

**WIRELESS COMMUNICATION NETWORKS FOR  
PROVIDING REMOTE MONITORING OF DEVICES**

**CROSS-REFERENCE TO RELATED APPLICATIONS**

5        This application is a continuation-in-part of the following U.S. utility patent applications: U.S. Patent Application Serial No. 09/812,809, filed March 20, 2001, and entitled "System and Method for Monitoring the Light Level in a Lighted Area," which is a continuation-in-part of U.S. Patent Application Serial No. 09/412,895, filed October 5, 1999, and entitled, "System and Method for Monitoring the Light Level  
10    Around an ATM," which is a continuation-in-part of U.S. Patent Application Serial No. 09/172,554, filed October 14, 1998, and entitled "System for Monitoring the Light Level Around an ATM;" U.S. Patent Application Serial No. 09/271,517, filed March 18, 1999, and entitled, "System For Monitoring Conditions in a Residential Living Community;" and U.S. Patent Application Serial No. 09/439,059, filed  
15    November 12, 1999, and entitled, "System and Method for Monitoring and Controlling Remote Devices." Each of the identified U.S. patent applications is incorporated herein by reference in its entirety.

**FIELD OF THE INVENTION**

20        The present invention generally relates to systems for monitoring and/or controlling a plurality of remote devices via a host computer connected to a wide area network (WAN), and more particularly relates to systems and methods for managing communication between the host computer and the plurality of remote devices.

**BACKGROUND OF THE INVENTION**

25        There are a variety of systems for monitoring and/or controlling any of a number of systems and/or processes, such as, for example, manufacturing processes, inventory systems, emergency control systems, personal security systems, residential systems, and electric utility meters to name a few. In many of these "automated  
30    monitoring systems," a host computer in communication with a wide area network monitors and/or controls a plurality of remote devices arranged within a geographical region. The plurality of remote devices typically use remote sensors and controllers to monitor and respond to various system parameters to reach desired results. A number

of automated monitoring systems use computers or dedicated microprocessors in association with appropriate software to process system inputs, model system responses, and control actuators to implement corrections within a system.

Various schemes have been proposed to facilitate communication between the host computer and the remote devices within the system, including RF transmission, light transmission (including infra-red), and control signal modulation over the local power distribution network. For example, U.S. Patent No. 4,697,166 to Warnagiris *et al.* describes a power-line carrier backbone for inter-element communications. As recognized in U.S. Patent No. 5,471,190 to Zimmerman, there is a growing interest in home automation systems and products that facilitate such systems. One system, critically described in the Zimmerman patent, is the X-10 system. Recognizing that consumers will soon demand interoperability between household systems, appliances, and computing devices, the Electronics Industry Association (EIA) has adopted an industry standard, known as the Consumer Electronics Bus (CEBus). The CEBus is designed to provide reliable communications between suitably configured residential devices through a multi-transmission media approach within a single residence.

One problem with expanding the use of control systems technology to distributed systems is the cost associated with developing the local sensor-actuator infrastructure necessary to interconnect the various devices. A typical approach to implementing control system technology is to install a local network of hard-wired sensors and actuators along with a local controller. Not only is there expense associated with developing and installing appropriate sensors and actuators, but the added expense of connecting functional sensors and actuators with the local controller is also problematic. Another prohibitive cost is the expense associated with the installation and operational expense associated with programming the local controller.

Accordingly, an alternative solution for implementing a distributed control system suitable for monitoring and controlling remote devices that overcomes the shortcomings of the prior art is desired.

### **SUMMARY OF THE INVENTION**

The present invention provides wireless communication networks for providing remote monitoring of devices. One embodiment of the present invention is

generally directed to a cost-effective automated monitoring system and method for monitoring and controlling a plurality of remote devices via a host computer connected to a communication network, such as a wide area network. The automated monitoring system may include one or more sensors to be read and/or actuators to be controlled, ultimately, through a remote applications server via a site controller. The remote applications server and the site controller may communicate via a communication network, such as a wide area network. The sensors and/or actuators are in communication with a plurality of wireless transceivers, which define a primary wireless communication network. The wireless transceivers may transmit and/or receive encoded data and control signals to and from the site controller. Additional communication devices, such as wireless repeaters, may relay information between the wireless transceivers disposed in connection with the sensors and/or actuators and the site controller.

The present invention may be viewed as a wireless communication network adapted for use in an automated monitoring system for monitoring and controlling a plurality of remote devices via a host computer connected to a wide area network. Briefly, in one embodiment, the wireless communication network may comprise a plurality of wireless transceivers having unique identifiers and a site controller. Each of the plurality of wireless transceivers may be configured to receive a sensor data signal from one of the plurality of remote devices and transmit an original data message using a predefined wireless communication protocol. The original data message may comprise the corresponding unique identifier and sensor data signal. Each of the plurality of wireless transceivers may be further configured to receive the original data message transmitted by one of the other wireless transceivers and transmit a repeated data message using the predefined communication protocol. The repeated data message may include the sensor data signal and the corresponding unique identifier. The site controller in communication with at least one of the plurality wireless transceivers, the site controller may be configured to: receive the original data messages and the repeated data messages; identify the remote device associated with the corresponding sensor data signal; and provide information related to the sensor data signal to the wide area network for delivery to the host computer.

The present invention may also be viewed as a wireless communication network for monitoring and controlling a plurality of remote devices. Briefly, in one

embodiment, the wireless communication network may comprise a plurality of wireless transceivers having unique identifiers. Each of the plurality of wireless transceivers may be configured to receive a sensor data signal from one of the plurality of remote devices and transmit an original data message using a predefined  
 5 wireless communication protocol. The original data message may comprise the corresponding unique identifier and sensor data signal. Each of the plurality of wireless transceivers may be configured to receive the original data message transmitted by one of the other wireless transceivers and transmit a repeated data message using the predefined communication protocol. The repeated data message  
 10 may include the sensor data signal and the corresponding unique identifier. Furthermore, at least one of the plurality of wireless transceivers may be further configured to provide the original data messages and the repeated data messages to a site controller connected to a wide area network. The site controller may be configured to manage communications between the wireless communication network  
 15 and a host computer connected to the wide area network.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

The accompanying drawings incorporated in and forming a part of the  
 20 specification, illustrate several aspects of the present invention, and together with the description serve to explain the principles of the invention. The components in the drawings are not necessarily to scale, emphasis instead being placed upon clearly illustrating the principles of the present invention. Moreover, in the drawings, like reference numerals designate corresponding parts throughout the several views.

25 FIG. 1 is a block diagram illustrating an embodiment of an automated monitoring system according to the present invention.

FIG. 2 is a block diagram of one of a number of embodiments of a transceiver of FIG. 1 in communication with a sensor of FIG. 1.

30 FIG. 3 is a more detailed schematic diagram illustrating the connectivity of the WAN of FIG. 1.

FIG. 4 is a block diagram illustrating one of a number of possible embodiments of the site controller of FIG. 1.

FIG. 5 is a table illustrating an embodiment of a message structure for a communication protocol according to the present invention that may be used for communicating between the site controller and transceivers of FIG. 1.

FIG. 6 is a table illustrating various values for the “to address” in the message structure of FIG. 5.

FIG. 7 illustrates three sample messages for the message structure of FIG. 5 according to the present invention.

FIG. 8 is a table illustrating the data section of a downstream message in accordance with the message protocol of FIG. 5.

FIG. 9 is a table illustrating the data section of an upstream message in accordance with the message protocol of FIG. 5.

FIG. 10 is a block diagram illustrating another embodiment of the automated monitoring system according to the present invention.

FIG. 11 is a block diagram illustrating the automated monitoring system of FIG. 1 being used as a primary backbone system for providing remote monitoring and/or controlling services to a secondary being used to providing monitoring being used to provide being implemented to one of a number of embodiments of a collection of wireless communication network for interconnected remote a plurality of remote devices in communication with the primary automated monitoring system of FIG. 1 according to the present invention.

### **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

Having summarized the invention above, reference is now made in detail to the description of the invention as illustrated in the drawings. While the invention will be described in connection with these drawings, there is no intent to limit it to the embodiment or embodiments disclosed therein. On the contrary, the intent is to cover all alternatives, modifications and equivalents included within the spirit and scope of the invention as defined by the appended claims.

FIG. 1 is a block diagram illustrating one of a number of possible embodiments of an automated monitoring system 100 according to the present invention. Automated monitoring system 100 may comprise one or more applications servers 110, a database 115, a wide area network (WAN) 120, transceivers/repeaters

125, sensor/actuators 130, transceivers 135, sensors 140, transmitters 145, and at least one site controller 150. Each of the sensor/actuators 130 and sensors 140 is integrated with a suitably configured wireless transceiver/repeater 125, a wireless transceiver 135, or wireless transmitter 145. Within the context of this document, a wireless  
 5 transceiver/repeater 125, a wireless transceiver 135, and a wireless transmitter 145 will be referred to as “wireless communication devices.”

Each of the wireless communication devices in automated monitoring system 100 is preferably small in size and may be configured to transmit a relatively low-power signal, such as, for example a radio frequency (RF) signal. As a result, in some  
 10 applications, the transmission range of a given RF communication device may be relatively limited. Of course, the transmitter power and range may be appropriately designed for the target operating environment. As will be appreciated from the description that follows, this relatively limited transmission range of the wireless communication devices is advantageous and a desirable characteristic of automated  
 15 monitoring system 100. Although the wireless communication devices are depicted without a user interface such as a keypad, *etc.*, in certain embodiments the wireless communication devices may be configured with user selectable pushbuttons, switches, an alphanumeric keypad, or any other type of user interface device suitably configured with software and/or firmware to accept operator input. Often the wireless  
 20 communication device will be in communication with a sensor 140 or with a sensor/actuator 130, such as a smoke detector, a thermostat, a security system, *etc.*, where user selectable inputs may not be needed.

As illustrated in FIG. 1, the wireless communication devices in automated monitoring system 100 are geographically arranged such that the antenna patterns (not  
 25 shown) associated with each wireless communication device overlap to create a coverage area 165. In this manner, automated monitoring system 100 may enable a site controller 150 associated with coverage area 165 to communicate with each sensor/actuator 130 and each sensor 140 via any of a plurality of possible communication paths. For instance, site controller 150 may communicate with a  
 30 specific sensor/actuator 130 via a plurality of distinct communication paths, each of which are defined by one or more wireless communication devices involved in the communication between site controller 150 and the specific sensor/actuator 130. By way of example, one of the plurality of possible communication paths may consist of

a wireless connection from site controller 150 to a wireless communication device associated with the specific sensor/actuator 130. Another possible communication path may consist of a wireless connection from site controller 150 to an intermediate wireless communication device and then to the wireless communication device associated with the specific sensor/actuator 130. Further communication paths may include multiple intermediate wireless communication devices in the wireless connection between site controller 150 and the wireless communication device associated with the specific sensor/actuator 130.

As illustrated in FIG. 1, one or more sensors 140 may communicate with at least one site controller 150 via a wireless transmitter 145, a wireless transceiver 135, or a wireless transceiver/repeater 125. Furthermore, one or more sensors/actuators 130 may communicate with at least one site controller 150 via a wireless transceiver 135 or a wireless transceiver/repeater 125. One of ordinary skill in the art will appreciate that in order to send a command from the applications server 110 to a sensor/actuator 130, the wireless communication device associated with the sensors/actuators 130 should be a two-way communication device, such as a transceiver. It will also be appreciated that one or more sensors/actuators 130 may be in direct communication with one or more site controllers 150. It will be further appreciated that the communication medium between the one or more sensor/actuators 130 and the one or more site controller 150 may be wireless or, for relatively closely located configurations, a wired communication medium may be used.

As is further illustrated in FIG. 1, automated monitoring system 100 may comprise a plurality of stand-alone wireless transceiver/repeaters 125. Each stand-alone wireless transceiver/repeater 125, as well as each wireless transceiver 135, may be configured to receive one or more incoming transmissions (transmitted by a remote transmitter 145 or transceiver 135) and to transmit an outgoing signal. This outgoing signal may be any wireless transmission signal, such as, for example, a low-power RF transmission signal, or a higher-power RF transmission signal. Alternatively, where a wired configured is employed, the outgoing signal may be transmitted over a conductive wire, fiber optic cable, or other transmission media. One of ordinary skill in the art will appreciate that if an integrated wireless communication device (*e.g.*, a wireless transmitter 145, a wireless transceiver 135, or a wireless transceiver/repeater 125) is located sufficiently close to site controller 150 such that its output signal can

be received by at least one site controller 150, the data transmission signal need not be processed and repeated through either a wireless transceiver/repeater 125 or wireless transceivers 135.

One or more site controllers 150 are configured and disposed to receive remote  
 5 data transmissions from the various stand-alone wireless transceiver/repeaters 125, integrated wireless transmitters 145, or the integrated wireless transceivers 135. The site controllers 150 may be configured to analyze the transmissions received, convert the transmissions into TCP/IP format, and further communicate the remote data signal transmissions via WAN 120 to one or more applications servers 110 or other devices  
 10 in communication with WAN 120. One of ordinary skill in the art will appreciate that additional site controllers 150 may function as either a back-up site controller in the event of a site controller failure or can function as a primary site controller to expand the potential size of coverage area 165 of automated monitoring system 100. When implemented as a back-up site controller 150, the second site controller 150 may  
 15 function when the applications server 110 detects a site controller failure. Alternatively, the second site controller 150 may function to expand the capacity of automated monitoring system 100. A single site controller 150 may accommodate a predetermined number of wireless communication devices. While the number of wireless communication devices may vary based upon individual requirements, in one  
 20 of a number of embodiments there may be approximately 500 wireless communication devices.

By way of example, a second site controller 150 may double the capacity of a single system. Although not shown, additional site controllers 150 may be added depending on the specific implementation of automated monitoring system 100. The  
 25 number of wireless communication devices managed by a site controller 150 is limited only by technical constraints such as memory, storage space, *etc.* In addition, the site controller 150 may manage more addresses than devices as some wireless communication devices may have multiple functions such as sensing, repeating, *etc.* As stated above, automated monitoring system 100 includes an applications server  
 30 110 in communication with site controller 150 via WAN 120. Applications server 110 may host any of a variety of application specific software depending on the precise environment in which automated monitoring system 100 is employed. As further described below, the site controller 150 may receive, via WAN 120,



information in the form of data and/or control signals from applications server 110, laptop computer 155, workstation 160, and any other device in communication with WAN 120. Site controller 150 may then communicate the data and/or control signals to remote sensor/actuators 130 and/or remote sensors 140. Automated monitoring system 100 may also comprise a database 115 associated with applications server 110. Database 115 may be configured to communicate with applications server 110 and record client specific data or to assist the applications server 110 in deciphering a particular data transmission from a particular sensor 140.

Reference is now made to FIG. 3, which is a block diagram illustrating a transceiver 135 that may be integrated with a sensor 130. As stated above, the characteristics of sensor 130 may vary depending on the environment in which automated monitoring system 100 is implemented. For example, the sensor 130 may be a two-state device such as a smoke alarm, a thermometer, a utility meter, a personal security system controller, or any other sensor. Regardless the specific characteristics of sensor 130, transceiver 135 may include a data interface 305 configured to receive and/or transmit signal to sensor 130. If the signal output from the sensor 130 is an analog signal, the data interface 305 may include an analog-to-digital converter (not shown) to convert the signals. Alternatively, where transceiver 135 and sensor 130 communicate using digital signals, transceiver 135 may include a digital interface (not shown) that communicates with the data interface 305 and the sensor 130.

As illustrated in FIG. 2, the sensor 140 may be in communication with the transceiver 135. Transceiver 135 may comprise an RF transceiver controller 210, a data interface 205, a microcontroller 215, a memory 220, and an antenna 225. A data signal forwarded from the sensor 140 may be received by the data interface 205. In those situations where the data interface 205 has received an analog data signal, the data interface 205 may be configured to convert the analog signal into a digital signal before forwarding a digital representation of the data signal to the data controller 215. In one embodiment, each transceiver 135 may be configured with a memory 220 that stores a unique transceiver identifier that identifies the RF transceiver 135.

Transceivers 135 that function in automated monitoring system 100 as both a repeater and an integrated transceiver have two unique addresses. One address indicates messages intended for the repeater; the second address indicates messages

for the sensor 140. Data controller 215 evaluates the incoming message to determine which address the message contains, which function is desired, and acts accordingly.

In operation, the RF transceiver 135 receives an incoming message via antenna 225. The transceiver controller 210 receives the incoming message, modifies the received signal, and passes the modified signal onto the microcontroller 215. The microcontroller 215 evaluates the message to determine the intended recipient.

If the intended recipient is the integrated transceiver 135, the microcontroller 215 then prepares the appropriate response as discussed below. This response may include data from the sensor 140. If the intended recipient is the repeater, the microcontroller 215 then prepares the message to be repeated onto the intended recipient according to the message protocol discussed below.

Of course, additional and/or alternative configurations may also be provided by a similarly configured transceiver 135. For example, a similar configuration may be provided for a transceiver 135 that is integrated into, for example, a carbon monoxide detector, a door position sensor, etc. Alternatively, system parameters that vary across a range of values may be transmitted by transceiver 135 as long as data interface 205 and microcontroller 215 are configured to apply a specific code that is consistent with the input from sensor 140. Automated monitoring system 100 may enable the target parameter to be monitored. The transceiver 135 may be further integrated with an actuator (not shown). This provides the ability to remotely control systems such as HVAC systems, lighting systems, *etc.* via the applications server 110 (FIG. 1). Further information regarding use of actuators in automated monitoring system 100 may be found in commonly assigned U. S. Patent Application Serial No. 09/811,076, entitled "System and Method for Monitoring and Controlling Remote Devices," and filed March 16, 2001, which is hereby incorporated in its entirety by reference.

One of ordinary skill in the art will appreciate that the various communication devices in automated monitoring system 100 may be configured with a number of optional power supply configurations. For example, a personal mobile transceiver may be powered by a replaceable battery. Similarly, a repeater may be powered by a replaceable battery that may be supplemented and/or periodically charged via a solar panel. These power supply circuits, therefore, may differ between communication device depending upon the devices being monitored, the related actuators to be

controlled, the environment, and the quality of service required. In the case of a transceiver acting as both a repeater and a remote monitoring device, the transceiver may be independently powered so as not to drain the sensor or actuator. Those skilled in the art will appreciate how to meet the power requirements of the various communication devices. As a result, it is not necessary to further describe a power supply suitable for each communication device and each application in order to appreciate the concepts and teachings of the present invention.

As stated above, automated monitoring system 100 may be used in a variety of environments to monitor and/or control any of a variety of types of sensors 140 and sensors/actuators 130. Regardless of the particular environment and the type of remote device employed in automated monitoring system 100, transceiver 135 may further comprise logic configured to receive data from sensor 140 and/or sensor/actuator 130, retrieve the unique identifier from memory 220, and generate a transmit message using a predefined communication protocol being implemented by the wireless communication network, which is described in detail below. Nonetheless, one of ordinary skill in the art will appreciate that various other communication protocols may be used in accordance with the present invention.

Depending on the specific implementation of sensor 140 and/or sensor/actuator 130, the data may be formatted in a variety of ways. For example, as stated above, the data received by data interface 205 may be an analog or a digital signal. Regardless the specific configuration of sensor 140 and/or sensor/actuator 130, data interface 205 is configured to receive the sensor data.

The transmit message generated may comprise the unique identifier stored in memory 220 and the sensor data. As described above, the transmit message may be formatted in the message structure described below. More importantly, the transmit message may be configured such that the transmit message may be received by the site controller 150 via the wireless communication network and such that the site controller 150 may identify the sensor 140 and/or sensor/actuator 130 and notify applications server 110 of the transmit message.

One of ordinary skill in the art will appreciate that the logic described above, may be implemented in hardware, software, firmware, or a combination thereof. As illustrated in FIG. 2, in one of a number of possible embodiments, the logic is implemented in software or firmware that is stored in memory 220 and that is

executed by microcontroller 215. If implemented in hardware, as in alternative embodiments, the logic may be implemented in any one or combination of volatile memory elements (*e.g.*, random access memory (RAM, such as DRAM, SRAM, SDRAM, *etc.*)) and nonvolatile memory elements (*e.g.*, ROM, hard drive, tape, CDROM, *etc.*). Memory 220 may incorporate electronic, magnetic, optical, and/or other types of storage media. Memory 220 may also have a distributed architecture, where various components are situated remote from one another. If implemented in hardware, as in alternative embodiments, the logic may be implemented with any or a combination of the following technologies, which are all well known in the art: a discrete logic circuit(s) having logic gates for implementing logic functions upon data signals, an application specific integrated circuit (ASIC) having appropriate combinational logic gates, a programmable gate array(s) (PGA), a field programmable gate array (FPGA), *etc.*

Furthermore, one of ordinary skill in the art will appreciate that the integration of sensor 140 and/or sensor/actuator 130 and transceiver 135 may be accomplished in a variety of ways. For example, in one embodiment, transceiver 135 may be included within sensor 140 and/or sensor/actuator 130 as part of its internal configuration. In other embodiments, transceiver 135 may be externally attached to sensor 140 and/or sensor/actuator 130. In further embodiments, transceiver 135 may be installed in close proximity to sensor 140 and/or sensor/actuator 130 such that transceiver 135 and sensor 140 and/or sensor/actuator 130 communicate via a wired or wireless connection.

Referring again to FIG. 2, during normal operation, transceiver 135 may receive a command message on antenna 225 via a message protocol. The command message may be initiated from site controller 150, applications server 110, laptop 155, workstation 160, or any other device connected to WAN 120. In this manner, the command message may be used to request data related to the electricity consumption of a particular electric meter 300. Microcontroller 215 may evaluate the received message to determine if the “to” address is its own unique address. If it is, then the microcontroller 215 evaluates the command and prepares a response message.

In response to the command message, microcontroller 215 receives the sensor data related to the sensor 140 and/or sensor/actuator 130. In one embodiment, the sensor data may be retrieved by initiating a request to the sensor 140 and/or

sensor/actuator 130. In another embodiment, the data may be stored in memory 220, in which case microcontroller 215 retrieves the data from memory 220. Microcontroller 215 may also retrieve the unique address from memory 220. Then, the microcontroller 215 formats a transmit signal in response to the command message as described above. Microcontroller 215 then communicates the transmit signal to transceiver controller 210, which provides the transmit signal to the wireless communication network. The transmit signal may be delivered to the site controller 150. Depending on where the command message was generated, the transmit signal may be forwarded to applications server 110, laptop 155, workstation 160, a computing device operated by a user, or any other device connected to WAN 120.

Of course, additional and/or alternative configurations may also be provided by a similarly configured transceiver. For example, a similar configuration may be provided for a transceiver that is integrated into, for example, a carbon monoxide detector, a door position sensor, etc. Alternatively, system parameters that vary across a range of values may be transmitted by transceiver 135 as long as data interface 205 and microcontroller 215 are configured to apply a specific code that is consistent with the input from sensor 140. As long as the code is known by the application server 110 or workstation 160, the target parameter may be monitored with the present invention. The RF transceiver 135 may be further integrated with an actuator. This would provide the user with the ability to remotely control systems such as HVAC systems, lighting systems, *etc.* remotely via the applications server 260. Further information regarding the integration of an actuator can be found in Serial No. 09/811,076, "System and Method for Monitoring and Controlling Remote Devices," filed March 16, 2001, commonly assigned and incorporated in its entirety herein by reference.

It will be appreciated by persons skilled in the art that the various RF communication devices illustrated and described may be configured with a number of optional power supply configurations. For example, a personal mobile transceiver may be powered by a replaceable battery. Similarly, a stand-alone RF transceiver/repeater may be powered by a replaceable battery that may be supplemented and/or periodically charged via a solar panel. These power supply circuits, therefore, may differ between RF communication devices depending upon the devices being monitored, the related actuators to be controlled, the environment, and

the quality level of service required. In the case of an RF transceiver acting as both a repeater and a remote monitoring device, the RF transceiver may be independently powered so as not to drain the sensor or actuator. Those skilled in the art will appreciate the various power requirements of the various RF communication devices.

5 As a result, it is not necessary to further describe a power supply suitable for each RF communication device and each application in order to appreciate the concepts and teachings of the present invention.

Reference is now made to FIG. 3, which illustrates the external connectivity of WAN 120 of FIG. 1 in accordance with the present invention. Site controller 150 may  
 10 be configured to transmit control signals and receive data signals using the open data packet protocol described in detail below. Site controller 150 is preferably interconnected permanently on WAN 120 and configured to receive data signals from the wireless communication devices and translate the data signals for transfer to applications servers 110 via WAN 120. Site controller 150 may translate the received  
 15 data signals into any appropriate protocol for delivery via WAN 120. For example, in one embodiment site controller 150 translates the received data signals into transmission control protocol/Internet protocol (TCP/IP) for delivery via WAN 120. As stated above, applications server 110 may be configured for communication with WAN 120 via, for example, router 310 and further protected and buffered by  
 20 firewall 320. Applications server 110 may also configured with web applications and client specific applications as needed for operation of automated monitoring system 100. Consistent with the concepts and teachings of the present invention, applications server 110 may be assisted in its task of storing and making available client specific data by database 115.

25 As further illustrated in FIG. 3, a client workstation 160 may include a Web browser for facilitating communication with applications server 110, database 115, and/or site controller 150. Alternatively, clients may access WAN 120 via a remote laptop 155 or other computing devices (not shown) configured with a compatible Web browser or other user interface. In this way, the applications server 110 may provide  
 30 client specific data upon demand.

As stated above, communication between site controller 150 and sensors/actuators 130 and sensors 140 is accomplished using an open data packet protocol in accordance with the present invention. Because the wireless

communication devices are geographically arranged such that their respective antenna patterns overlap to create a coverage area 165, site controller 150 may communicate with each sensor/actuator 130 and each sensor 140 via any of a plurality of possible communication paths. Each of the communication paths are defined by one or more

5 wireless communication devices involved in the communication between site controller 150 and the target sensor/actuator 130 and/or sensor 140. For instance, site controller 150 may communicate with a specific sensor/actuator 130 via a plurality of distinct communication paths. By way of example, one of the plurality of possible communication paths may consist of a wireless connection from site controller 150 to

10 a wireless communication device associated with the specific sensor/actuator 130. Another possible communication path may consist of a wireless connection from site controller 150 to an intermediate wireless communication device and then to the wireless communication device associated with the specific sensor/actuator 130. Further communication paths may include multiple intermediate wireless

15 communication devices in the wireless connection between site controller 150 and the wireless communication device associated with the specific sensor/actuator 130. In this manner, site controller 150 may communicate with sensors/actuators 130 and/or sensors 140 that are located a greater distance from the site controller 150 by having messages repeated by successive wireless communication devices along one of the

20 communication paths.

Having illustrated and described the operation of the various combinations of communication devices with the sensor 140 and sensor/actuators 130 (FIG. 1), reference is now made to FIG. 4, which is a block diagram further illustrating one embodiment of a site controller 150. A site controller 150 may comprise an

25 antenna 405, a transceiver controller 410, a central processing unit (CPU) 415, memory 420, a network interface device, such as a network card 425, a digital subscriber line (DSL) modem 430, an integrated services digital network (ISDN) interface card 435, as well as other components not illustrated in FIG. 4, which may be configured to enable a TCP/IP connection to the WAN 120 (FIG. 1). Site

30 controller 150 may also include a power supply 450 for powering the site controller 150. The power supply 450 may be one of many known power supplies. In addition, the site controller 150 may include an on-site input port 455, which allows a technician to communicate directly with site controller 150. Further information

regarding the function, operation, and architecture of the site controller 150 may be found in commonly assigned U. S. Patent Application "System and Method for Controlling Communication Between a Host Computer and Communication Devices Associated with Remote Devices in an Automated Monitoring System," (Serial  
 5 No. 09/xxx,xxx) which is hereby incorporated in its entirety by reference.

The transceiver controller 410 may be configured to receive incoming transmissions via the antenna 405. Each of the incoming transmissions are consistently formatted in the message protocol as described below. The site controller 150 may be configured such that the memory 420 includes a look-up table 425  
 10 configured for identifying the various remote and intermediate communication devices used in generating and transmitting the received data transmission. As illustrated in FIG. 4, site controller 150 may include an "Identify Remote Transceiver" memory sector 440 and and "Identify Intermediate Transceiver" memory sector 445. Programmed or recognized codes within memory 425 may also be provided and  
 15 configured for controlling the operation of a CPU 415 to carry out the various functions that are orchestrated and/or controlled by the site controller 150. For example, memory 420 may include program code for controlling the operation of the CPU 415 to evaluate an incoming data packet to determine what action needs to be taken. In this regard, one or more look-up tables 425 may also be stored within the  
 20 memory 420 to assist in this process. Furthermore, the memory 420 may be configured with program code configured to identify a remote transceiver or identify an intermediate RF transceiver. Function codes and RF transmitter and/or RF transceiver identifiers may all be stored with associated information within the look-up tables 425.

Thus, one look-up table 425 may be provided to associate transceiver identifications with a particular user. Another look-up table 425 may be used to associate function codes associated with the message protocol. For example, a look-up table 425 may include a unique code designating various functions, such as test, temperature, smoke alarm active, security system breach, *etc.* In connection with the  
 30 lookup table(s) 425, the memory 420 may also include a plurality of code segments that are executed by the CPU 415, which may in large part control operation of the site controller 150. For example, a first data packet segment may be provided to access a first lookup table to determine the identity of the transceiver that transmitted



the received message. A second code segment may be provided to access a second lookup table to determine the proximate location of the transceiver that generated the message. A third code segment may be provided to identify the content of the message transmitted (not shown). Namely, is it a fire alarm, a security alarm, an emergency request by a person, a temperature control setting, *etc.* In accordance with the present invention, additional, fewer, or different code segments may be provided to carry out different functional operations and data signal transfers.

The site controller 150 may also include one or more network interface devices to facilitate via WAN 120. For example, the site controller 150 may include a network card 425, which may allow the site controller 150 to communicate across a local area network to a network server. This network server may function as a backup site controller 150 to the WAN 120. Alternatively, the site controller 150 may contain a DSL modem 430, which may be configured to provide a link to a remote computing system by way of the public switched telephone network (PSTN). In yet another embodiment, the site controller 150 may include an ISDN card 435 configured to communicate via an ISDN connection with a remote system. One of ordinary skill in the art will appreciate that various other communication interfaces may be provided to serve as primary and/or backup links to the WAN 120 (FIG. 1) or to local area networks that might serve to permit local monitoring of the status of the site controller 150 and for data packet control.

Communication between the site controller 150 and the communication devices within coverage area 165 may be implemented using a data packet protocol according to the present invention. FIG. 5 sets forth one embodiment of a message structure for the data packet protocol of the present invention. Messages transmitted within the automated monitoring system 100 may consist of a “to” address 500, a “from” address 510, a packet number 520, a number of packets in a transmission 530, a packet length 540, a message number 550, a command number 560, data 570 (if applicable), and a check sum error detectors (CKH 580 and CKL 590).

The “to” address 500 indicates the intended recipient of the packet. This address can be scalable from one to six bytes based upon the size and complexity of automated monitoring system 100. By way of example, the “to” address 500 may indicate a general message to all transceivers, to only the repeaters, or to a single integrated transceiver. In a six byte “to” address 500, the first byte indicates the

transceiver type – to all transceivers, to some transceivers, or a specific transceiver. The second byte may be the identification base, and bytes three through six may be used for the unique transceiver address (either stand-alone or integrated). The “to” address 500 may be scalable from one byte to six bytes depending upon the intended recipient(s).

The “from” address 510 identifies the transceiver originating the transmission and may be a six-byte unique address. The “from” address 510 may be the address of the site controller 150 (FIG. 1) when the site controller 150 (FIG. 1) requests data, or this may be the address of the integrated transceiver responding to a request for information from the site controller 150 (FIG. 1).

The packet number 520, the packet maximum 530, and the packet length 540 may be used to concatenate messages that are greater than a predetermined length. The packet maximum 530 indicates the number of packets in the message. The packet number 520 may be used to indicate a packet sequence number for a multiple-packet message.

The message number 550 may be assigned by the site controller 150. Messages originating from the site controller 150 may be assigned an even number, while responses to the site controller 150 may have a message number equal to the original message number plus one. Thus, the site controller 150 may increment the message number 550 by two for each new originating message. This may enable the site controller 150 to coordinate the incoming responses to the appropriate command message.

The command number 560 may designate a specific data request from the receiving device. One of ordinary skill in the art will appreciate that, depending on the specific implementation of automate monitoring system 100, the types of commands may differ. In one embodiment, there may be two types of commands: device specific and non-device specific. Device specific commands may control a specific device such as a data request or a change in current actuator settings. Commands that are not device specific may include, but are not limited to, a ping, an acknowledge, a non-acknowledgement, downstream repeat, upstream repeat, read status, emergency message, and a request for general data to name a few. General data may include a software version number, the number of power failures, the number of resets, *etc.*

The data field 570 may contain data as requested by a specific command. The requested data may be any value. By way of example, test data can preferably be encoded in ASCII (American Standard Code for Information Interchange) or other known encoding systems as known in the art. The data field 570 of a single packet may be scalable up to a predetermined length. When the requested data exceeds the predetermined length, the data controller of transceiver 135 may divide the data into an appropriate number of sections and concatenates the series of packets for one message using the packet identifiers as discussed above.

While specific byte lengths for sections of the message are being set forth, it would be obvious to one of ordinary skill in the art to vary the byte lengths based upon system needs. Less complex systems, *etc.* could use smaller sized sections, whereas more complex systems could increase the byte lengths.

Checksum fields 580 and 590 may be used to detect errors in the transmissions. In one embodiment, any error can be detected via cyclic redundancy check sum methodology. This methodology treats the message as a large binary number and divides the binary number by a generating polynomial (such as CRC-16). The remainder of this division is then sent with the message as the checksum. The receiver then calculates a checksum using the same methodology and compares the two checksums. If the checksums do not match, the packet or message will be ignored. While this error detection methodology is preferred, one of ordinary skill in the art will appreciate that other error detection systems may be implemented.

As stated above, automated monitoring system 100 may employ wireless and/or wired communication technologies for communication between site controller 150 and the various communication devices. In one embodiment, communication between site controller 150 and the communication devices may be implemented via an RF link at a basic rate of 4,800 bits per second (bps) and a data rate of 2400 bps. All the data may be encoded in the Manchester format such that a high to low transition at the bit center point represents a logic zero and a low to high transition represents a logic one. One of ordinary skill in the art will appreciate that other RF formats may be used depending upon design needs. By way of example, a quadrature phase shift encoding method may be used, thereby enabling automated monitoring system 100 to communicate via hexadecimal instead of binary.

While the message indicates specific byte length for each section, only the order of the specific information within the message is constant. The byte position number in individual transmissions may vary because of the scalability of the “to” address 500, the command byte 560, and the scalability of the data 570.

5       The message may further include a preface and a postscript (not shown). The preface and postscripts are not part of the message body but rather serve to synchronize the control system and to frame each packet of the message. The packet begins with the preface and ends with a postscript. The preface may be a series of twenty-four logic ones followed by two bit times of high voltage with no transition.  
10   The first byte of the packet can then follow immediately. The postscript may be a transition of the transmit data line from a high voltage to a low voltage, if necessary. It may be less desirable to not leave the transmit data line high after the message is sent. It would be obvious to one of ordinary skill in the art to modify the preface and the postscript as necessary based on specific design needs.

15       FIG. 6 sets illustrates one embodiment of a byte assignment for the “to” address 500 of FIG. 5. One of ordinary skill in the art will appreciate that various byte assignments may be used within “to” address field 500. For example, in one embodiment, “to” address 500 consists of six bytes. The first byte (Byte 1) may indicate the device type. The second byte (Byte 2) may indicate the manufacturer or  
20   the owner. The third byte (Byte 3) may be a further indication of the manufacturer or owner. The fourth byte (Byte 4) may indicate either that the message is for all devices or that the message is for a particular device. If the message is for all devices, the fourth by may be a particular code. If the message is for a particular device, the fourth, fifth, and sixth bytes (Byte 5 and Byte 6) may include the unique identifier for  
25   that particular device.

FIG. 7 illustrates three sample messages using the open data packet protocol described above. The first message 700 illustrates the broadcast of an emergency message “FF” from a central server with an address “0012345678” to a integrated transceiver with an address of “FF.”

30       The second message 702 illustrates how the first message 700 may be sent to a stand-alone wireless communication device. In this manner, emergency message “FF” from a central server with address “00123456578” is first sent to stand-alone wireless device “FO.” The second message 702, further contains additional command data

“A000123456” that may be used by the wireless communication device to identify further wireless communication devices to send the signal through on the way to the destination device.

The third message 704 illustrates how the open data packet protocol of the present invention may be used to “ping” a remote wireless communication device in order to determine the status of the wireless communication device. In this manner, source unit “E112345678” originates a ping request by sending command “08” to a transceiver identified as “A012345678.” The response to the ping request may be as simple as reversing the “to address” and the “from address” of the command such that a healthy wireless communication device may send a ping message back to the originating device. Automated monitoring system 100 may be configured to expect a return ping within a specific time period. Operators of automated monitoring system 100 may use the delay between the ping request and the ping response to model system loads and to determine if specific system parameters might be adequately monitored and controlled with the expected feedback transmission delay.

Returning to FIG. 1, the repeater 125 acts as a communications bridge between a remote device and the site controller 150 when the remote device cannot reliably communicate directly with the site controller 150. In this manner, the repeater 125 may communicate in two or more modes: normal, emergency, *etc.*

For example, during normal communication, the repeater 125 may have two functions: repeating messages (including repeating upstream messages) and repeating downstream messages. Upstream messages are transmissions to another repeater 125 or remote device. Downstream messages are transmissions to another repeater 125 or site controller 150. Responding to common messages involves taking the appropriate action and sending a response to the site controller 150. The repeater 125 may modify the message depending upon the stream direction. An exemplary format for the data field 570 (FIG. 5) for a downstream repeated message is set forth in FIG. 8. For instance, the data field 570 may have a “Num Index” 810, which may identify the number of indexes being sent with the downstream repeat. The indexes 820 may contain the downstream path including the intended recipient address. The “CMD” field 830 may identify the particular command for the intended receiving device. The “Data for last CMD” field 840 may include either an index table of downstream addresses or upstream addresses.

FIG. 9 sets forth an example of the structure for the data field 570 (FIG. 5) of an upstream message. The “number of repeaters” 910 may indicate the number of upstream repeaters. The “Repeater Retry Counters” 920 may indicate the number of retries by each repeater in the upstream. The “CMD” field 930 may indicate the command sent to the intended remote device. The “Data for last CMD” 940 may indicate the data in response to the original command from the intended remote device.

Examples of commands that are sent directly from the site controller 150 to the repeater 125 include load upstream addresses. This command causes the repeater 125 to store the addresses to which the repeater 125 sends messages when communicating upstream. The loading of the upstream addresses also initiates a transceiver functioning as a repeater 125. The response to a load command may be a status message that is sent to the site controller 150.

Another example of a communication mode is emergency mode. In this mode, emergency messages are automatically transmitted upstream regardless of what other actions may be taking place. Unlike normal communications, emergency messages are sent unsolicited from the integrated transceiver 135 to the site controller 150.

During all modes of communication, each of the communication devices may expect a response message to all messages sent. There may be at least two acknowledgements: a positive acknowledgement, a negative acknowledgement, *etc.* The positive acknowledgement may be sent whenever a message is received and understood. A negative acknowledgement may be sent whenever the message is not received and understood correctly or whenever an expected message is not received. A negative acknowledgment may be followed by a predetermined number of retries.

Further information regarding the structure and operation of the data packet protocol implemented in automated monitoring system 100 may be found in commonly assigned U. S. Patent Application “System and Method for Interconnecting Remote Devices in an Automated Monitoring System,” (Atty. Docket No. 081607-1160) which is hereby incorporated in its entirety by reference.

Referring again to FIG. 1, during normal operations, the site controller 150 acts as the communications master. Thus, the site controller 150 may initiate all communications with the wireless communications devices, except emergency messages described below. In addition to initiating command messages, the site

controller 150 also tracks response messages. This tracking allows the site controller 150 to monitor the operational status of the wireless communication devices.

In addition to orchestrating communications with the wireless communication devices, the site controller 150 maintains current databases of information regarding the automated monitoring system 100, such as, for example, the function of the wireless communication devices, the unique address for each of the wireless communication devices, and current data contained in response messages. One of ordinary skill in the art will appreciate that site controller 150 may contain information related to any of a variety of other aspects of automated monitoring system 100.

As stated above, the site controller 150 also controls communications with the applications server 110. When communicating with the applications server 110, the site controller 150 receives requests for information, commands, *etc.* and sends the appropriate response. The applications server 110 maintains the requested information and/or commands in such a way that a user can access the information via a remote desktop 155, remote laptop 160, or any other device configured for communication with WAN 120.

Furthermore, the site controller 150 may be configured to maintain a database of the wireless communication devices and their unique addresses. The unique addresses may be assigned such that the site controller 150 may easily send messages to one wireless communication device, a group of wireless communication devices, or all of the wireless communication devices.

Using the site controller 150 as a communications master and maintaining individual device information at the site controller 150 enables the wireless communication devices to be simplified. The simplification of the wireless communication devices has two main advantages: (1) simplifying the construction of the wireless communication device and (2) decreasing cost. The wireless communication device may be simplified because of a reduced need for large memory and/or storage devices. As well-known in the art, memory and storage devices increase in cost as they increase in size. Therefore, decreasing the size of the memory and/or storage reduces the construction and operating costs of the wireless communication devices.

The site controller 150 sends messages to the wireless communication devices using the open data packet protocol described above. Initially, the site controller 150 maps all of the wireless communication devices so as to “learn” all the unique addresses and the necessary communication paths. To do this mapping, the site controller 150 issues a command to document the down-stream addresses and the up-stream addresses for each communication path associated with a wireless communication device. The site controller 150 logs the response data from the wireless communication devices into the appropriate databases. Messages from the site controller 150 travel downstream to the intended wireless communication device(s). Messages from the wireless communication devices(s) travel upstream to the site controller 150. When mapping the communication paths for each of the wireless communication devices, the site controller 150 “learns” the unique address of each wireless communication device, the addresses of each wireless communication device that can directly and reliably communicate with each transceiver/repeater(s) 125 in a downstream path, the unique address of each transceiver/repeater(s) 125 in a downstream path, the upstream addresses for the wireless communication device, and the downstream addresses for the wireless communication device.

When sending command messages, the site controller 150 expects an acknowledgement to each command. A command is considered to be not acknowledged when either the site controller 150 fails to receive a positive acknowledgement from the addressed wireless communication device within a first time period, fails to detect the re-transmission of the command message by a transceiver/repeater 125 within a second time period, or receives a negative acknowledgement from a transceiver/repeater 125 in the communication path of the wireless communication device. If the site controller 150 receives a negative acknowledgement, the site controller 150 can then log the failed message and retransmit the message. This re-transmission can occur a predetermined number of times. It should be noted the first time period may be longer than the second time period. In the above cases, the first time period is long enough to ensure receipt of the preamble of the response message when there are multiple transceiver/repeater(s) 125 in the communications path. The second time period is long enough to either receive the preamble of the response message (if no repeaters are in the communications path) or to hear the preamble of the command message being re-transmitted by the first



transceiver/repeater 125 in the communication path of the wireless communication device.

After initializing and during normal operation, the site controller 150 may poll each of the remote sensor/actuators according to a predetermined schedule. During this process, the site controller 150 requests the current operating status of each of the sensors/actuators 135. The status of a sensor/actuator device 135 depends upon the type of device. For example, a smoke detector's status may be operational/non-operational. In contrast, a utility meter's status may be the utility usage that has occurred since the last polling. A thermostat's status response may be the actual temperature and the desired temperature. The information sent in response to a status poll may vary depending upon the particular configuration of the sensor/actuator 135. This information is maintained by the site controller 150 and may be sent to the applications server 110 upon request. The predetermined schedule has flexibility based upon the number of failed attempts and any emergency messages. To poll the device, the site controller 150 sends a "read status" message. The command message is considered complete upon receipt of the response message. The command message is considered failed upon receipt of a negative acknowledgement. After a negative acknowledgement, the site controller 150 retries the command six more times and logs all failed attempts.

To facilitate communications with the applications server 110, the site controller 150 may maintain database files of information. The site controller 150 may maintain communication databases that store the device failures, as discussed above, and that store the emergency messages. These database stored logs can contain the unique address of the wireless communication device, a code representing a present condition, and a date/time stamp. Any failures to communicate with the applications server 110 are also logged into the appropriate database. These databases may have a predetermined size and may be forwarded to the applications server 110 when the databases are a specific percentage full or upon request by the applications server 110. Once forwarded to and acknowledged by the applications server 110, the entries in the communications databases are deleted. One of ordinary skill in the art will appreciate that the contents, size, and scheduling of database entries may be varied in a variety of ways.

After mapping the wireless communication devices, the site controller 150 develops and maintains a database that includes the unique address for each wireless communication device, the number of transceiver/repeaters 125 in the downstream path, the address of each transceiver/repeater 125 in the downstream path, the upstream addresses, and the downstream addresses. The site controller 150 does not necessarily respond to the messages from wireless communication devices not listed in this database.

In addition to mapping the wireless communication devices, the site controller 150 may update the device database via the applications server 110. This update may add/delete wireless communication devices from the automated monitoring system 100, change the communications path of any or all of the wireless communication devices, or change the unique addresses of any or all of the wireless communication devices. Upon request of the applications server 110, the site controller 150 may transmit the device database to the applications server 110.

It should be noted that the databases enumerated above are merely exemplary, and other databases may be included as would be obvious to one of ordinary skill in the art.

The “normal” operating procedure described above is continued unless the site controller 150 receives an emergency message from a wireless communication device. The emergency message is transmitted unsolicited. The emergency message can be received by the site controller 150 either directly, via a repeater, or via a plurality of repeaters. Upon receipt of an emergency message, the site controller 150 immediately notifies the applications server 110 of the emergency message. In addition, the site controller 150 suspends the above polling for a predetermined time period. This suspension insures the receipt of any additional emergency messages. After the time period expires with no additional messages, the site controller 150 resumes polling.

To facilitate communications between the applications server 110 and the site controller 150, the site controller 110 maintains a database of contact information. By way of example, if the site controller 150 communicates via a network interface device 240, the site controller 150 can maintain a database of telephone numbers and IP addresses of the applications server 110.

During normal communications, the applications server 110 sends response messages. As stated above, one of ordinary skill in the art will appreciate that the

applications server 110 and the site controller 150 may communicate via TCP/IP protocol or any other protocol. Exemplary requests include a “get file” request of the database and a “put file” request, which sends a file to the site controller 150.

Normal communications between the site controller 150 and the applications server 110 may also be interrupted by an emergency message. The emergency message originates at the site controller 150 and may include an emergency message from a remote device, a “file too large” message, and a site controller status change message to name a few. In the case of safety and security system devices such as smoke detectors, glass break alarms, *etc.*, the site controller 150 may immediately generate an emergency message to the applications server 110 in the event a safety/security device fails to respond to a poll message.

FIG. 10 sets forth an alternate embodiment of an automated monitoring system 100. Automated monitoring system 100 of FIG. 1 is shown with an additional sensor 180 and transceiver 185. The additional sensor 180 and transceiver 185 are shown to be communicating with, but outside of, the coverage area 165. In this example, the additional sensor 180 and transceiver 185 may be placed outside of the original control system. In order to communicate, the coverage area of transceiver 185 need only overlap the coverage area 165. By way of example only, the original installation may be an automated monitoring system 100 that monitors electricity usage via the utility meters in an apartment complex. Later a neighbor in a single family residence nearby the apartment complex may remotely monitor and control their thermostat by installing a sensor/actuator transceiver according to the present invention. The transceiver 185 then communicates with the site controller 150 of the apartment complex. If necessary, repeaters (not shown) can also be installed to communicate between the transceiver 185 and the apartment complex site controller 150. Without having the cost of the site controller 150, the neighbor may enjoy the benefits of the control system.

FIG. 11 illustrates an automated monitoring network 1100 according to the present invention for enabling multiple groups of remote devices associated with multiple wireless communication networks to be monitored and/or controlled via a common connection to a wide area network, such as a WAN 120. As illustrated in FIG. 11, automated monitoring network 1100 comprises a primary automated monitoring system, such as automated monitoring system 100, and a secondary

wireless communication network 1110 in communication with automated monitoring system 100 . Automated monitoring system 100 may operate and be configured as described above.

For example, automated monitoring system 100 may comprise a plurality of remote devices to be monitored and/or controlled, a plurality of communication devices, such as transceivers 125 and 135, a site controller 150, a WAN 120, and a host computer, such as an applications server 110, a laptop 155, or a workstation 160. Each of the plurality of remote devices may be in communication with one of the plurality of communication devices such that a primary wireless communication network is defined within coverage area 165. In this manner, the primary wireless communication network associated with automated monitoring system 100 provides communication between each of the remote devices within coverage area 165 and the site controller 150. Hereinafter, the remote devices associated with automated monitoring system 100 will be referred to as the first group of remote device.

Secondary wireless communication network 1110 may comprise a second group of remote devices to be monitored and/or controlled and a plurality of communication devices, such as transceivers 125 and 135. Each of the second group of remote devices in secondary wireless communication network 1110 may be in communication with one of the plurality of communication devices such that the secondary wireless communication network 1110 is defined within coverage area 1120. Secondary wireless communication network 1110 may operate and be configured in a manner similar to the primary wireless communication network of automated monitoring system 100. For example, secondary wireless communication network 1110 may employ transceivers 125 and 135 as described above. Secondary wireless communication network 1110 may also employ the communication protocol described above. Nonetheless, one of ordinary skill in the art will appreciate that other transceivers and other communication protocols may be employed.

As illustrated in FIG. 11, automated monitoring system 100 includes one or more site controllers 150 that manage communications with applications server 110 via WAN 120. Significantly, automated monitoring network 1100 according to the present invention enables the secondary wireless communication network 1110 to access WAN 120 via the primary wireless communications network. Thus, the secondary wireless communication network 1110 does not have to use a separate site

controller 150 in order to communicate with applications servers 110, laptop 155, workstation 160, or other computing devices connected to WAN 120. Instead, the secondary wireless communication network 1110 may access the site controller 150 in automated monitoring system 100 via the primary wireless communication network.

- 5 For example, at least one of the communication devices in the secondary wireless communication network 1110 may communicate with at least one of the communication devices in automated monitoring system 100. In this manner, messages may be exchanged between the site controller 150 of the primary wireless communication network and the second group of remote devices, thereby enabling the
- 10 second group of remote devices to be monitored and/or controlled via the site controller 150 and/or the various computing devices connected to WAN 120.

The transceivers in automated monitoring system 100 and secondary wireless communication network 1110 may be configured to receive data signals from other devices and/or appliances via other wireless technologies, such as Bluetooth and the

15 802.11(b) standard adopted by the Institute of Electrical and Electronics Engineers (IEEE), which is hereby incorporated by reference in its entirety. For instance, the transceivers may be configured to implement the technology described in "Specification of the Bluetooth System: Specification Volume 1," February 22, 2001, which is hereby incorporated by reference in its entirety. In addition, infrared,

20 ultrasonic, and other types of wireless transceivers may be employed as one of ordinary skill in the art will appreciate.

One of ordinary skill in the art will appreciate that automated monitoring network 1100 provides a number of advantages for monitoring and/or controlling remote devices. For example, automated monitoring network 1100 reduces the

25 expense associated with monitoring and/or controlling the second group of remote devices in the secondary wireless communication network 1110. Specifically, the automated monitoring network 1100 according to the present invention eliminates the need for a separate site controller 150 and separate access to WAN 120. Furthermore, automated monitoring network 1100 promotes cooperative relationships between

30 organizations providing remote monitoring.

By way of example, automated monitoring system 100 may be used by an organization to enable customers to monitor and/or control a first group of remote devices. For instance, automated monitoring system 100 may be used to provide

individual residences in a managed apartment complex with the ability to remotely monitor and/or control a residential application, such as a residential security system. As described above and illustrated in FIG. 1, in this example automated monitoring system 100 may enable residents of the apartment complex to monitor and/or control the status of their residential security system via a laptop 155, workstation 160, or other computing device in communication with WAN 120.

Automated monitoring network 1100 enables a second group of remote devices associated with secondary wireless communication network 1110 to be monitored and/or controlled without obtaining a separate site controller 150 and separate access to WAN 120. As stated above, the secondary wireless communication network 1110 may access WAN 120 via the primary automated monitoring system 100. For example, in the above example, the second group of remote devices associated with secondary wireless communication network 1110 may be the electric meters for each of the residences in the managed apartment complex. The electric utility company that provides service to the managed apartment complex may desire to provide remote monitoring to the residents. Automated monitoring network 1100 according to the present invention enables the electric utility company to easily provide remote monitoring of the electric meters to the residents.

For instance, the electric utility company does not have to establish an independent automated monitoring system 100. Rather, the electric utility company only needs to establish a secondary wireless communication network 1110 as described above. Each of the electric meters may be communicatively coupled to a wireless transceiver, such as a transceiver 125 and transceiver 135 described above. In order to ensure communication throughout the entire coverage area 1120 of the electric meters associated with the secondary wireless communication network 1110, it may be necessary to implement additional wireless transceivers and/or repeaters as described above. In this manner, the collection of wireless transceivers associated with the electric meters defines the secondary wireless communication network 1110. As mentioned above, secondary wireless communication network 1110 may operate and be configured in a manner similar to the primary wireless communication network of automated monitoring system 100.

Given the existence of the secondary wireless communication network 1110, the electric utility company may provide remote monitoring of the electric meters to

the residents via the automated monitoring system 100 for monitoring and/or controlling the residential security systems. The only requirement is that at least one of the wireless transceivers associated with the electric meters is in communication with at least one of the wireless transceivers associated with the residential security systems. Data messages related to the secondary wireless communication system 1110 may be passed through the primary wireless communication network to the site controller 150 and on to applications server 110 via WAN 120, thereby enabling the electric meters to be monitored and/or controlled via the site controller 150 and/or the various computing devices connected to WAN 120.

One of ordinary skill in the art will appreciate that the secondary wireless communication network 1110 and the automated monitoring system 100 may employ any of a variety of types of remote devices. Accordingly, the specific needs of the secondary wireless communication network 1110 and the automated monitoring system 100 may differ. For example, secondary wireless communication network 1110 and the automated monitoring system 100 may differ only in the type of devices being monitored and/or controlled. As in the above example of one of many possible embodiments, coverage area 165 of automated monitoring system 100 and coverage area 1120 of secondary wireless communication network 1110 may be substantially overlapping. However, in other embodiments of automated monitoring network 1100, coverage area 165 and coverage area 1120 only have to overlap such that at least one transceiver from both secondary wireless communication network 1110 and automated monitoring system 100 communicate.

One of ordinary skill in the art will appreciate that what has been described herein is a very top-level illustration of a system constructed in accordance with the automated monitoring system 100 and the automated monitoring network 1100 of the present invention. In accordance with the invention, a variety of remote devices, such as utility meter devices, personal security devices, household devices and appliances, and other remote devices employing a sensor and/or an actuator, may be monitored and/or controlled from a remote location via a computing device connected to WAN 120. The data and command transmissions may be transmitted and received by the site controller 150 connected to WAN 120. Site controller 150 is further in communication with the wireless communication devices within coverage area 165. The data and command transmissions may be relayed via the various wireless

communication devices defining the communication path until they reach a designated destination or the site controller 150.

It will be further appreciated that automated monitoring system 100 in accordance with the present invention may be used in a variety of environments. In one embodiment, automated monitoring system 100 may be employed to monitor and record utility usage by residential and industrial customers, to transfer vehicle diagnostics from an automobile via a wireless transceiver integrated with the vehicle diagnostics bus to a local transceiver that further transmits the vehicle information through a local gateway onto a WAN, to monitor and control an irrigation system, to automate a parking facility, to monitor and control a residential security system, *etc.*, which are described in more detail in the commonly assigned U. S. Patent Application entitled, "System and Method for Monitoring and Controlling Residential Devices," issued Serial No. 09/704,150.

Automated monitoring system 100 may be adapted to monitor and apply control signals in an unlimited number of applications. By way of example only, the wireless communication devices may be adapted for use with any associated device, such as, for example, pay type publicly located telephones, cable television set top boxes, utility meters, and residential appliances and/or devices to enable a remote controllable home automation and security system.

In a geographic area appropriately networked with permanently located stand-alone transceivers 125, personal transceivers (not shown) may be used to monitor and control personnel access and egress from specific rooms or portions thereof within a controlled facility. Personal transceivers may further be configured to transfer personal information to public emergency response personnel, to transfer personal billing information to vending machines, or to monitor individuals within an assisted living community.

Wireless communication devices using the open data packet protocol of the present invention may be integrated to monitor and control a host of industrial and business applications as well. By way of example only, building automation systems, fire control systems, alarm systems, industrial trash compactors, and building elevators may be monitored and controlled. In addition, courier drop boxes, time clock systems, automated teller machines, self-service copy machines, and other self-service devices may be monitored and controlled as appropriate. By way of further



example, a number of environment variables that require monitoring may be integrated with automated monitoring system 100 to permit remote monitoring and control. For instance, light levels in the area adjacent to automated teller machines must meet minimum federal standards. Also, the water volume transferred by water treatment plant pumps, smokestack emissions from a coal burning power plant, or a coke fueled steel plant oven may be remotely monitored.

The wireless communication devices using the open data packet protocol of the present invention may be further integrated with a voice-band transceiver having multiple function buttons. As a result, when a person presses, for example, the emergency button on his/her transmitter, medical personnel, staff members, or others may respond by communicating via two-way radio with the party in distress. In this regard, each transceiver may be equipped with a microphone and a speaker that would allow a person to communicate information such as their present emergency situation, their specific location, *etc.*

The foregoing description has been presented for purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise forms disclosed. Obvious modifications or variations are possible in light of the above teachings. For example, it should be appreciated that, in some implementations, the transceiver unique address is not necessary to identify the location of the transceiver. Indeed, in implementations where the transceiver is permanently integrated into an alarm sensor other stationary device within a system, then the applications server 110 and/or the site controller 150 may be configured to identify the transmitter location by the transmitter unique address alone. It will be appreciated that, in embodiments that do not utilize wireless transceiver/repeaters 125, the wireless transmitters 145 and/or wireless transceivers 135 may be configured to transmit at a higher power level, in order to effectively communicate with the site controller 150.

The embodiment or embodiments discussed were chosen and described to illustrate the principles of the invention and its practical application to enable one of ordinary skill in the art to utilize the invention in various embodiments and with various modifications as are suited to the particular use contemplated. All such modifications and variations are within the scope of the invention as determined by

the appended claims when interpreted in accordance with the breadth to which they are fairly and legally entitled.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219  
2220  
2221  
2222  
2223  
2224  
2225  
2226  
2227  
2228  
2229  
2230  
2231  
2232  
2233